

SFP Optical Module


Industrial 1.25G Single-mode 1xSC Optical Fiber 3km (Receiver 1550TX 1310RX)

This is an Industrial SFP optical module. It uses a single mode optical fiber and the speed rate can up to 1.25Gbps, transmission distance up to 3 km. This product need to use in pair and match up with fiber converter and optical Ethernet switch with SFP port, it can be used in Ethernet, telecom and optical fiber communication and other industries...

Feature

- Use SFP packaging form, SC connector, support SFF8472 standard;
- Support hot plug ;
- Use 1550nm FP laser and 1310nm PIN-TIA;
- The data transmission distance of single mode optical fiber can up to 3 km;
- Data input and output ports are comply with the low voltage emitter coupled logic(LVPECL) standard;
- Low electromagnetic interference to the environment, strong ESD protection;
- Meet IEC-60825 laser safety standard;
- Meet RoHS standard.

Board diagram



Installation step

Please check the following items before installation. If any missing, please contact the dealer.

- SFP Optical Module 1pc
- User manual 1pc

Please follow the following step

- 1) Please turn off the signal source and the device's power, installation with power on may damage the device;
- 2) Plug SFP optical module into SFP socket;
- 3) Check if the installation is correct and device is good, make sure all the connection is reliable and power up the system;
- 4) Make sure the optical communication is normal.

■ Specification

Item		Description
Power	Power Supply	The Host Power Supply
	Voltage Range	DC 3.15V ~ 3.45V
	Consumption	1W
Optical Characteristics	Optical Wave Length	1550nm TX / 1310nm RX;
	Emission Light Power	-8 ~ 0 dBm
	Receiver Sensitivity	-22 dBm
Transmission Characteristics	Optical Fiber Type	Single mode 9/125um
	Optical Fiber Port	1xSC
	Transmission Distance	Single mode 3km
Protection	ESD	1a contact discharge 3 level 1b air discharge 3 level Per: IEC61000-4-2
Environmental	Working Temperature	-40°C~85°C
	Storage Temperature	-40°C~85°C
	Humidity (Non-condensing)	0~95%
Mechanical	Dimension (L×W×H)	55.4mm×13.7mm×6.25mm
	Material	Stainless steel
	Color	White
	Weight	17g

Product are subject to change without prior notice

■ Trouble Shooting

Please find the following solution when the device doesn't work

- Please confirm if the installation is correct;
- Please confirm the module plugged is match with the requirement;
- If the problem still exist, please contact the factory.