



Remote Paging Console

T-8000A



Features

- * The T-8000A remote paging console is connected with T-8000 through universal industrial standard CAT 5 for zone announcement or communication at a remote and different location from the control center.
- * Each controller provides four RJ45 ports for the remote paging console.
- * The CAT 5 wiring is not only featured of cost-effective, convenient layout, but also integration of RS 485 communication and audio transmission together.
- * Extra DC 24V power supply.
- * Eight zone selector with state indication.
- * Talk and all zone paging swift keys are provided.
- * 2 and 4 tones chimes with selector and off switch.
- * Volume controls are provided for chime and microphone.
- * Full indications includes individual zone, all zone, busy, paging, power, output level to provide a direct visualization.

Specifications

| | |
|---------------------------|---|
| Model | T-8000A |
| MIC | Condenser Microphone |
| Frequency Response | 50Hz~18KHz (± 2 dB) |
| S/N Ratio | Better than 75dB |
| THD | Less than 0.1% at 1KHz, |
| Signal Output | 0.775V/600 Ω |
| Mic Input | 5mV/600 Ω |
| Indication | Individual zone, all zone, busy, paging, power, output level indicators |
| Protection | DC+24V/2A, Revert fuse protection |
| Power Supply | DC 24V |
| Power Consumption | 5W |
| Weight | 2.22Kg |
| Dimensions | 200 x 142.7 x 51.5mm |